







DESCRIZIONE:

Tappi per ALTE TEMPERATURE.

MATERIALE:

- Silicone resistente Fino a 315 °C.
- Colore standard :Neutro.

Tutte le misure sono espresse in millimetri.

| Articolo | Ø D | Н | Filetto | Colore | Conf. (pz) |
|----------|-----|------|---------|--------|------------|
| CS-1 | 0.5 | 12.7 | | Neutro | 1000 |
| CS-2 | 0.9 | 12.7 | | Neutro | 1000 |
| CS-3 | 1 | 19 | | Neutro | 1000 |
| CS-4 | 1.6 | 19 | | Neutro | 1000 |
| CS-5 | 1.8 | 25.4 | M2 | Neutro | 1000 |
| CS-6 | 2 | 19 | | Neutro | 1000 |
| CS-7 | 2.4 | 12.7 | | Neutro | 1000 |
| CS-8 | 2.4 | 19 | | Neutro | 1000 |
| CS-9 | 2.5 | 12.7 | М3 | Neutro | 1000 |
| CS-10 | 2.5 | 25.4 | М3 | Neutro | 1000 |
| CS-11 | 2.8 | 12.7 | | Neutro | 1000 |
| CS-12 | 2.8 | 19 | | Neutro | 1000 |
| CS-13 | 3.2 | 12.7 | | Neutro | 1000 |
| CS-14 | 3.2 | 25.4 | | Neutro | 1000 |
| CS-15 | 3.5 | 25.4 | | Neutro | 1000 |
| CS-16 | 3.6 | 12.7 | | Neutro | 1000 |
| CS-17 | 3.6 | 25.4 | | Neutro | 1000 |
| CS-18 | 3.8 | 12.7 | M4 | Neutro | 1000 |
| CS-19 | 3.8 | 19 | M4 | Neutro | 1000 |
| CS-20 | 3.8 | 25.4 | M4 | Neutro | 1000 |
| CS-21 | 4 | 12.7 | | Neutro | 1000 |
| CS-22 | 4 | 25.4 | | Neutro | 1000 |
| CS-23 | 4.2 | 25.4 | | Neutro | 1000 |
| CS-24 | 4.4 | 12.7 | | Neutro | 1000 |
| CS-25 | 4.4 | 25.4 | | Neutro | 1000 |
| CS-26 | 4.4 | 38.1 | | Neutro | 1000 |



TAPPI IN GOMMA TIPO " CS " PER ALTE TEMPERATURE

| Articolo | Ø D | Н | Filetto | Colore | Conf. (pz) |
|----------|------|------|---------|--------|------------|
| CS-27 | 4.6 | 25.4 | | Neutro | 1000 |
| CS-28 | 4.8 | 12.7 | M5 | Neutro | 1000 |
| CS-29 | 4.8 | 25.4 | M5 | Neutro | 1000 |
| CS-30 | 5 | 12.7 | | Neutro | 500 |
| CS-31 | 5.5 | 25.4 | | Neutro | 500 |
| CS-32 | 5.7 | 12.7 | M6 | Neutro | 500 |
| CS-33 | 5.7 | 19 | M6 | Neutro | 500 |
| CS-34 | 5.7 | 25.4 | M6 | Neutro | 500 |
| CS-35 | 5.7 | 38.1 | М6 | Neutro | 500 |
| CS-36 | 5.9 | 12.7 | | Neutro | 500 |
| CS-37 | 5.9 | 25.4 | | Neutro | 500 |
| CS-38 | 5.9 | 38.1 | | Neutro | 500 |
| CS-39 | 6.4 | 25.4 | | Neutro | 500 |
| CS-40 | 6.6 | 25.4 | | Neutro | 500 |
| CS-41 | 7.1 | 25.4 | | Neutro | 500 |
| CS-42 | 7.5 | 12.7 | M8 | Neutro | 500 |
| CS-43 | 7.5 | 19 | M8 | Neutro | 500 |
| CS-44 | 7.5 | 25.4 | M8 | Neutro | 500 |
| CS-45 | 7.5 | 38.1 | M8 | Neutro | 500 |
| CS-46 | 7.9 | 25.4 | | Neutro | 500 |
| CS-47 | 7.9 | 38.1 | | Neutro | 500 |
| CS-48 | 8.6 | 25.4 | | Neutro | 500 |
| CS-49 | 9 | 38.1 | | Neutro | 500 |
| CS-50 | 9.5 | 19 | M10 | Neutro | 500 |
| CS-51 | 9.5 | 25.4 | M10 | Neutro | 500 |
| CS-52 | 9.5 | 38.1 | M10 | Neutro | 500 |
| CS-53 | 10.3 | 25.4 | | Neutro | 500 |
| CS-54 | 11.1 | 25.4 | | Neutro | 500 |
| CS-55 | 11.6 | 19 | M12 | Neutro | 500 |
| CS-56 | 11.6 | 25.4 | M12 | Neutro | 500 |
| CS-57 | 11.6 | 38.1 | M12 | Neutro | 500 |
| CS-58 | 11.9 | 25.4 | | Neutro | 500 |
| CS-59 | 11.9 | 38.1 | | Neutro | 500 |
| CS-60 | 12.2 | 38.1 | | Neutro | 500 |
| CS-61 | 12.7 | 38.1 | | Neutro | 500 |
| CS-62 | 13.6 | 38.1 | M14 | Neutro | 250 |
| CS-63 | 13.6 | 76.2 | M14 | Neutro | 250 |
| CS-64 | 14.3 | 38.1 | | Neutro | 250 |
| CS-65 | 15.2 | 38.1 | M16 | Neutro | 250 |
| CS-66 | 15.9 | 38.1 | M16 | Neutro | 250 |
| CS-67 | 15.9 | 63.5 | M16 | Neutro | 250 |
| CS-68 | 17.4 | 38.1 | M18 | Neutro | 250 |
| CS-69 | 18.5 | 38.1 | | Neutro | 250 |
| CS-70 | 19 | 38.1 | | Neutro | 250 |
| CS-71 | 19 | 50.8 | | Neutro | 250 |
| CS-72 | 19 | 88.9 | | Neutro | 250 |
| CS-73 | 19.8 | 38.1 | | Neutro | 250 |
| CS-74 | 20.6 | 38.1 | | Neutro | 250 |
| CS-75 | 22.2 | 38.1 | | Neutro | 250 |
| CS-76 | 23.8 | 38.1 | | Neutro | 250 |
| CS-77 | 24.6 | 38.1 | | Neutro | 250 |
| CS-78 | 25.4 | 38.1 | | Neutro | 250 |
| CS-79 | 25.4 | 50.8 | | Neutro | 250 |



TAPPI IN GOMMA TIPO " CS " PER ALTE TEMPERATURE

| Articolo | Ø D | Н | Filetto | Colore | Conf. (pz) |
|----------|------|------|---------|--------|------------|
| CS-80 | 27 | 38.1 | | Neutro | 100 |
| CS-81 | 28.6 | 38.1 | | Neutro | 100 |
| CS-82 | 30.2 | 38.1 | | Neutro | 100 |
| CS-83 | 31.8 | 38.1 | | Neutro | 100 |
| CS-84 | 34.3 | 38.1 | | Neutro | 100 |
| CS-85 | 35 | 38.1 | | Neutro | 100 |
| CS-86 | 38.1 | 25.4 | | Neutro | 100 |
| CS-87 | 38.1 | 44.5 | | Neutro | 50 |
| CS-88 | 41.3 | 50.8 | | Neutro | 50 |
| CS-89 | 44.5 | 50.8 | | Neutro | 50 |
| CS-90 | 47.6 | 50.8 | | Neutro | 50 |
| CS-91 | 50.8 | 50.8 | | Neutro | 50 |
| CS-92 | 53.5 | 50.8 | | Neutro | 50 |

01/09/2009

Mar-Gom S.a.s. si riserva il diritto di modificare senza preavviso la progettazione e la realizzazione dei prodotti presenti in questo catalogo. info@mar-gom.it (3 www.mar-gom.it